

VIDEX®

VIDEX VLF-H025C 330Lm 5000K

INDEX: VLF-H025C

TECHNISCHE KARTE



WIEDERAUFLADBARE LED-SCHEINWERFER



Gemäß den Bestimmungen des WEEE-Gesetzes ist es verboten, Altgeräte, die mit dem Symbol einer durchgekreuzten Mülltonne gekennzeichnet sind, zusammen mit anderen Abfällen zu entsorgen. Der Benutzer, der elektronische und elektrische Geräte abgeben möchte, ist verpflichtet, diese an einer Sammelstelle für Altgeräte abzugeben. Das Gerät enthält keine gefährlichen Bestandteile, die sich besonders negativ auf die Umwelt und die menschliche Gesundheit auswirken.

VIDEX®



Not Dimmable



Free



IP65

GARANTIE 2 JAHRE

NEUTRAL WHITE



5000K

Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálna biela / Neutraal wit / Semleges feher / Nevrtralno bela / Neutralno bijela / Neutralweiß / Alb neutru / Neutralus balta / Neitrāls balta / Neutraalne valge / Неутрално бяла / Bianco neutro.

General parameters

Austauschbare Lichtquelle nein

Art der Lichtquelle

Dimmbar nein

Technologie LED

Elektrische Parameter

Leistung 5 W + COB

Verbindungsschnittstelle Micro USB

Photometrische Parameter

Nutzlichtstrom der Lichtquelle (Φ_{use}) 310 Lm

Farbtemperatur des Lichts 5000K (neutralweiß)

Spitzenlichtintensität 1380 cd

VIDEX VLF-H025C 330Lm 5000K

INDEX: VLF-H025C

Zusätzliche Information

Farbe des Gehäuses	Schwarz
Umgebungstemperaturbereich	-20° +40°C
Quecksilbergehalt	nein
Schutzklasse, IP	IP65
Gehäusematerial	Polycarbonat (PC)

Maße

Strichcode	4820246481076
Höhe	46 mm
Breite	70 mm
Tiefe	38 mm
Menge in der Kiste	20 Stück
Einheit Nettogewicht	99g
Im Paket	1 Stk.

Warenkennzeichnungsschilder

Verpackungskennzeichnung CE, Entsorgungsmethode

VIDEX®

VIDEX VLF-H025C 330Lm 5000K

INDEX: VLF-H025C



VIDEX[®]

VIDEX VLF-H025C 330Lm 5000K

INDEX: VLF-H025C

INDEX: VLF-H025C



VIDEX®
MODEL | H025C

RECHARGEABLE LED HEADLAMP WITH SENSOR

310
MAX LUMENS

- 1800mAh RECHARGEABLE
- DUAL LIGHT
- IP65
- 1m SHOCKPROOF
- RED LIGHT

VIDEX®
MODEL | H025C

MAIN LED CREE XTE 5W 5000K (Neutral white)

LOW BEAM LED COB 5W 5000K (Neutral white)

85° Beam angle and 74m max illumination distance.
120° Beam angle and 7m max illumination distance.
Both light sources can work together reaching max brightness 310 lumens.

VIDEX®

VIDEX VLF-H025C 330Lm 5000K

INDEX: VLF-H025C



VIDEX®

VIDEX VLF-H025C 330Lm 5000K

INDEX: VLF-H025C



VIDEX®

VIDEX VLF-H025C 330Lm 5000K

INDEX: VLF-H025C

VIDEX®

MICRO-USB PORT

MODEL | H025C



Full charge for around 3 hours.
The charging port covered by thick silicone, which prevents dust and water penetrate inside the device.

VIDEX®

1800mAh. 600 CYCLES

MODEL | H025C



Built-in Li-polymer rechargeable can run for around 10 hours at one cycle and can replace thousands of primary batteries during its service life. An intelligent charge control circuit protects the battery from overdischarge and overcharge.

VIDEX®

NYLON HEADBAND

MODEL | H025C



The headband is made of nylon, which is an elastic and wear-resistant material.

VIDEX®

TILT MECHANISM

MODEL | H025C



Adjust the headlamp tilt angle within 45 degrees.



VIDEX VLF-H025C 330Lm 5000K

INDEX: VLF-H025C

VIDEX
MODEL | H025C

1. Maximum power mode 250 LM
2. Minimum power mode 95 LM
3. COB mode (low beam) 75 LM
4. COB+Maximum power 310 LM
5. SOS/STROBE mode
6. Red light
7. Red flashing light

VIDEX PROGRAM ROOT
MODEL | H025C

SENSOR BUTTON

- Start position: OFF → Action A: Press → Result: SENSOR HIGH / SENSOR COB → Action B: Hand wave → Result: OFF/ ON
- Start position: * HIGH / LOW / STROBE / RED ON / RED FLASH / COB → Action A: Press → Result: SENSOR * → Action B: Hand wave → Result: OFF/ ON*
- Start position: ON/OFF → Action A: Press and hold for 0.5 sec → Result: Battery status

ON/OFF BUTTON

- Start position: OFF → Action A: Press → Result: > ON HIGH > LOW > STROBE > RED ON > RED FLASH > OFF >
- Start position: ON/OFF → Action A: Press and hold for 0.5 sec → Result: COB ON → Action B: Press and hold for 0.5 sec → Result: COB OFF

* Sensor remembers current lighting mode and applies it until the sensor mode will be deactivated.
Notes: The modes selection performs within 5 seconds. After this time, the next short press will turn off the light.
The headlamp automatically memorizes the last selected lighting mode (except COB mode) and applies it next time when turned on.
The Main Light modes and Flood Light (COB) mode can be turned on together unless the sensor is activated.

VIDEX LIGHTING MODES
MODEL | H025C

LIGHTING MODES	HIGH	LOW	COB	COB+HIGH	STROBE
OUTPUT	250 Lm	95 Lm	75 Lm	310 Lm	95 Lm
RUNTIME	4h 50min	9h	10h 20min	3h	21h
DISTANCE	74m	46m	7m	74m	46m
INTENSITY	1380cd	520cd	12cd	1380cd	520cd
	RED ON	1.2 Lm / 8h	RED FLASH	1.2 Lm / 16h	

VIDEX KIT CONTENT
MODEL | H025C

USER'S MANUAL HEADLAMP HEADBAND CHARGING CABLE

SIZES 70x46x38mm
WEIGHT: 99g (including headband)

Technische Änderungen vorbehalten. Die darin enthaltenen Daten Material ist nicht rechtlich bindend.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11, 30-732 Krakow, Polen.