

VIDEX®

VIDEX VLF-A105RH 1200Lm 5000K

INDEX: VLF-A105RH

TECHNISCHE KARTE



WIEDERAUFLADBARE LED-TASCHENLAMPE



Gemäß den Bestimmungen des WEEE-Gesetzes ist es verboten, Altgeräte, die mit dem Symbol einer durchgekreuzten Mülltonne gekennzeichnet sind, zusammen mit anderen Abfällen zu entsorgen. Der Benutzer, der elektronische und elektrische Geräte abgeben möchte, ist verpflichtet, diese an einer Sammelstelle für Altgeräte abzugeben. Das Gerät enthält keine gefährlichen Bestandteile, die sich besonders negativ auf die Umwelt und die menschliche Gesundheit auswirken.

VIDEX®



Not Dimmable



Free



IP66

GARANTIE 3 JAHRE

NEUTRAL WHITE



5000K

Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálna biela / Neutraal wit / Semleges feher / Nevrnalno bela / Neutralno bijela / Neutralweiß / Alb neutru / Neutralus balta / Neitrāls balta / Neutraalne valge / Неутрално бяла / Bianco neutro.

General parameters

Austauschbare Lichtquelle nein

Art der Lichtquelle

Dimmbar nein

Technologie LED

Elektrische Parameter

Leistung 10 W

Verbindungsschnittstelle USB-C

Photometrische Parameter

Nutzlichtstrom der Lichtquelle (Φ_{use}) 1200 Lm

Farbtemperatur des Lichts 5000K (neutralweiß)

Spitzenlichtintensität 5200 cd

VIDEX VLF-A105RH 1200Lm 5000K

INDEX: VLF-A105RH

Zusätzliche Information

Farbe des Gehäuses	Schwarz
Umgebungstemperaturbereich	-20° +40°C
Quecksilbergehalt	nein
Schutzklasse, IP	IP66
Gehäusematerial	Aviation anodized aluminum

Maße

Strichcode	4820246481007
Höhe	127 mm
Breite	28 mm
Tiefe	28 mm
Menge in der Kiste	20 stück
Einheit Nettogewicht	83g
Im Paket	1 Stk.

Warenkennzeichnungsschilder

Verpackungskennzeichnung CE, Entsorgungsmethode

VIDEX[®]

VIDEX VLF-A105RH 1200Lm 5000K

INDEX: VLF-A105RH

VIDEX[®]

VIDEX VLF-A105RH 1200Lm 5000K

INDEX: VLF-A105RH

VIDEX®

VIDEX VLF-A105RH 1200Lm 5000K

INDEX: VLF-A105RH



VIDEX®
MODEL | A105RH

MULTITASKING RECHARGEABLE
LED FLASHLIGHT

1200
MAX LUMENS

- SWIVEL HEAD
- TYPE-C
- IP66
- 1m IMPACT RESISTANCE

VIDEX®

VIDEX VLF-A105RH 1200Lm 5000K

INDEX: VLF-A105RH



VIDEX®

VIDEX VLF-A105RH 1200Lm 5000K

INDEX: VLF-A105RH



VIDEX®

MODEL | A105RH

VIDEX®

MODEL | A105RH

ANODIZED METAL SWITCH



Switch on/off the light, select the modes, and lock the flashlight. Press and hold for quick access to strobe mode. The flashlight's scheme memorizes the previously selected lighting mode (except strobe mode) and applies it at a next power-on.



VIDEX®

MODEL | A105RH

Water resistance IP66 gives reliable protection from any precipitation.

VIDEX®

MODEL | A105RH

INTEGRATED FOUR-LEVEL LED BATTERY INDICATOR



CHARGE
100-85%



CHARGE
85-50%



CHARGE
50-25%



CHARGE
25-1%

VIDEX®

VIDEX VLF-A105RH 1200Lm 5000K

INDEX: VLF-A105RH



VIDEX®

VIDEX VLF-A105RH 1200Lm 5000K

INDEX: VLF-A105RH

VIDEX®
MODEL A105RH



Scratch resistant tempered glass lens easily stands against high temperatures.

VIDEX®
MODEL A105RH



Copper-made springs keep flexible over the years and guarantee a firm contact.

VIDEX®
MODEL A105RH



WITH BATTERY 2200mAh

	TURBO	HIGH	MIDDLE	LOW	MOON	SOS
OUTPUT	1200 Lm	700 Lm	420 Lm	220 Lm	30 Lm	700 Lm
RUNTIME	1h*	1h 30min	2h 35min	5h 40min	80h	2h
DISTANCE	135m	104m	80m	57m	30m	104m
INTENSITY	5200cd	2680cd	1608cd	816cd	300cd	2680cd

The above output parameters tested with the stock battery Videx 18650 2200mAh and may vary due to conditions and actual batteries used.
*Turbo mode output levels may be reduced by the overheat control system.

VIDEX® PROGRAM ROOT
MODEL A105RH



Notes: The flashlight automatically memorizes the last selected lighting mode (excluding Strobe mode) and applies it next time when turned on. Battery indication is always on if the light is switched on.

VIDEX[®]

VIDEX VLF-A105RH 1200Lm 5000K

INDEX: VLF-A105RH

Technische Änderungen vorbehalten. Die darin enthaltenen Daten Material ist nicht rechtlich bindend.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,
30-732 Krakow, Polen.