

VIDEX®

VIDEX VLF-A505C 5500Lm 5000K

INDEX: VLF-A505C

TECHNISCHE KARTE

**WIEDERAUFLADBARE LED-TASCHENLAMPE**

Gemäß den Bestimmungen des WEEE-Gesetzes ist es verboten, Altgeräte, die mit dem Symbol einer durchgekreuzten Mülltonne gekennzeichnet sind, zusammen mit anderen Abfällen zu entsorgen. Der Benutzer, der elektronische und elektrische Geräte abgeben möchte, ist verpflichtet, diese an einer Sammelstelle für Altgeräte abzugeben. Das Gerät enthält keine gefährlichen Bestandteile, die sich besonders negativ auf die Umwelt und die menschliche Gesundheit auswirken.

VIDEX®



Not Dimmable



Free



IP68

GARANTIE 3 JAHRE

NEUTRAL WHITE



5000K

Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálna biela / Neutraal wit / Semleges feher / Nevrtralno bela / Neutralno bijela / Neutralweiß / Alb neutru / Neutralus balta / Neitrāls balta / Neutraalne valge / Неутрално бяла / Bianco neutro.

General parameters

Austauschbare Lichtquelle nein

Art der Lichtquelle

Dimmbar nein

Technologie LED

Elektrische Parameter

Leistung 20 W

Verbindungsschnittstelle USB-C

Photometrische Parameter

Nutzlichtstrom der Lichtquelle (Φ_{use}) 5500 Lm

Farbtemperatur des Lichts 5000K (neutralweiß)

Spitzenlichtintensität 20800 cd

VIDEX VLF-A505C 5500Lm 5000K

INDEX: VLF-A505C

Zusätzliche Information

Farbe des Gehäuses	Schwarz
Umgebungstemperaturbereich	-20° +40°C
Quecksilbergehalt	nein
Schutzklasse, IP	IP68
Gehäusematerial	Aviation anodized aluminum

Maße

Strichcode	4820246483209
Höhe	144 mm
Breite	49 mm
Tiefe	26 mm
Menge in der Kiste	20 stück
Einheit Nettogewicht	163g
Im Paket	1 Stk.

Warenkennzeichnungsschilder

Verpackungskennzeichnung CE, Entsorgungsmethode

VIDEX®

VIDEX VLF-A505C 5500Lm 5000K

INDEX: VLF-A505C

VIDEX[®]

VIDEX VLF-A505C 5500Lm 5000K

INDEX: VLF-A505C

VIDEX®

VIDEX VLF-A505C 5500Lm 5000K

INDEX: VLF-A505C



VIDEX®
MODEL | A505C

EXTRA HIGH POWER RECHARGEABLE FLASHLIGHT

5500
MAX LUMENS

- LONG-RANGE BEAM 500M
- FLUX STABILIZATION
- IP68
- 1m SHOCKPROOF

VIDEX®
MODEL | A505C

4X LUMINUS SST40
20W
5000K (Neutral white)

Excellent performance with four powerful LED chips. Maximum luminous flux 5500 Lumen, long-range beam distance up to 500 meters and high intensity 20800cd.

VIDEX®

VIDEX VLF-A505C 5500Lm 5000K

INDEX: VLF-A505C



VIDEX®

VIDEX VLF-A505C 5500Lm 5000K

INDEX: VLF-A505C

VIDEX®
MODEL | A505C

INTEGRATED FOUR-LEVEL LED BATTERY INDICATOR



CHARGE 100-85% CHARGE 85-50% CHARGE 50-25% CHARGE 25-1%

VIDEX®
MODEL | A505C

PROTECTION GRADE IP68



The flashlight can work stably when immersed for 30 minutes at a depth of up to 2 meters.

VIDEX®
MODEL | A505C

FAST CHARGE PORT TYPE-C




Charge the battery 4000mAh directly inside the flashlight for around 2.5 hours. Silicone cover protects the charging port from dust and water.

VIDEX®
MODEL | A505C

TEMPERED GLASS



Tempered glass withstands high temperatures, is resistant to scratches, and is not subject to yellowing.

VIDEX®

VIDEX VLF-A505C 5500Lm 5000K

INDEX: VLF-A505C



VIDEX®
MODEL | A505C

PROGRAM ROOT

Start position	Action A	Result	Action B	Result
OFF	Press and hold for 0.5 sec	ON	Press and hold for 0.5 sec	OFF
ON	Click	> MOON > LOW > MIDDLE > HIGH > TURBO >		
ON/OFF	Press and hold for 3 sec	STROBE	Click	Exit
OFF	Click	Battery status		
OFF	Double click	Lock	Double click	Unlock

Notes: The flashlight automatically memorizes the last selected lighting mode (excluding Strobe mode) and applies it next time when turned on. Battery indication is always on if the light is switched on.

VIDEX®
MODEL | A505C

KIT CONTENT

- SPARE SILICONE RINGS
- 18650 ADAPTER
- USER'S MANUAL, WARRANTY CARD
- LI-ION BATTERY
- FLASHLIGHT
- CHARGING CABLE
- LANYARD

SIZE 144x49mm
WEIGHT 163g (without battery)

Technische Änderungen vorbehalten. Die darin enthaltenen Daten Material ist nicht rechtlich bindend.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11, 30-732 Krakow, Polen.

Datum: 1.11.2024